

An Open Problem in Dynamic Edge Coloring

Martín Costa

University of Warwick

Abstract

This is an open problem in dynamic edge coloring that was presented at Dagstuhl Seminar 24471 - Graph Algorithms: Distributed Meets Dynamic.

The Setting

Let $G = (V, E)$ be a simple, undirected graph with n vertices, m edges and maximum degree Δ . It was shown by [Viz64] that the graph G can always be *edge colored* with at most $\Delta + 1$ colors. Furthermore, such a coloring can be computed in near-linear time in the *static* setting [ABB⁺24].

The dynamic setting: In the *dynamic* setting, we have a fixed set of n vertices V , and the graph G evolves over time via a sequence of edge insertions and deletions. We assume that we have some fixed value Δ and that the maximum degree of G is at most Δ at all times. Our objective is to design an algorithm that *explicitly* maintains an edge coloring χ of G at all times and has a small *update time*, which is the time it takes to update the edge coloring χ after an edge is either inserted or deleted from the graph G . We also define the *recourse* of an update as the number of edges that change color while handling the update. Since our algorithm explicitly maintains the edge coloring χ , the recourse of an update is a lower bound on the time it takes to handle that update.

The state-of-the-art for dynamic edge coloring: It is known how to maintain a $(1 + \epsilon)\Delta$ -edge coloring in $\tilde{O}(\text{poly}(1/\epsilon))$ worst-case update time against an adaptive adversary [DHZ19, Chr23] and in $O(\text{poly}(1/\epsilon))$ amortized update time against an oblivious adversary [BCPS24b].

The Open Problem

It is natural to ask if one can improve on these results. As a first step, we can ignore update time and consider only recourse, and see whether or not we can maintain a $(\Delta + o(\Delta))$ -edge coloring with only $\tilde{O}(1)$ recourse. More specifically, one can ask the following question.

Q1: Is it possible to maintain a $(\Delta + \tilde{O}(\Delta^{1-\gamma}))$ -edge coloring of a dynamic graph G with $\tilde{O}(1)$ recourse, for $\gamma > 0$?

This question is open even considering *amortized recourse* and an *oblivious adversary*. By a standard reduction, we can also assume that the graph is bipartite [KS87]. We remark that [BCPS24a] show how to maintain a $(\Delta + O(\alpha))$ -edge coloring with $\tilde{O}(1)$ update time, where α is the *arboricity* of the graph. This answers Q1 for graphs of sufficiently small arboricity.

Possible Hardness

A result of [CHL⁺20] shows that there exists a graph G such that, for any $\mu = O(\Delta)$, there exists a $(\Delta + \mu)$ -edge coloring χ of G with an uncolored edge e such that extending χ to e requires changing the colors of $\tilde{\Omega}(\Delta/\mu)$ edges. This implies that any analysis which does not consider the structure of the edge coloring maintained by a dynamic algorithm will not be sufficient to answer Q1. We remark that many of the current state-of-the-art dynamic algorithms for this problem are analysed in this way, and assume that the edge coloring of the graph is completely arbitrary at the start of each update [DHZ19, Chr23, BCPS24a]. If this lower bound can be extended to get an analogous bound in the dynamic setting, it would essentially rule out the possibility of obtaining faster dynamic algorithms for this problem.

References

- [ABB⁺24] Sepehr Assadi, Soheil Behnezhad, Sayan Bhattacharya, Martín Costa, Shay Solomon, and Tianyi Zhang. Vizing’s theorem in near-linear time. *CoRR*, abs/2410.05240, 2024.
- [BCPS24a] Sayan Bhattacharya, Martín Costa, Nadav Panski, and Shay Solomon. Arboricity-Dependent Algorithms for Edge Coloring. In *19th Scandinavian Symposium and Workshops on Algorithm Theory (SWAT)*, volume 294 of *LIPICs*, pages 12:1–12:15, 2024.
- [BCPS24b] Sayan Bhattacharya, Martín Costa, Nadav Panski, and Shay Solomon. Nibbling at Long Cycles: Dynamic (and Static) Edge Coloring in Optimal Time. In *Proceedings of the ACM-SIAM Symposium on Discrete Algorithms (SODA)*. SIAM, 2024.
- [CHL⁺20] Yi-Jun Chang, Qizheng He, Wenzheng Li, Seth Pettie, and Jara Uitto. Distributed Edge Coloring and a Special Case of the Constructive Lovász Local Lemma. *ACM Trans. Algorithms*, 16(1):8:1–8:51, 2020.
- [Chr23] Aleksander Bjørn Grodt Christiansen. The Power of Multi-step Vizing Chains. In *Proceedings of the 55th Annual ACM Symposium on Theory of Computing (STOC)*, pages 1013–1026. ACM, 2023.
- [DHZ19] Ran Duan, Haoqing He, and Tianyi Zhang. Dynamic edge coloring with improved approximation. In *30th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)*, 2019.
- [KS87] Howard J Karloff and David B Shmoys. Efficient parallel algorithms for edge coloring problems. *Journal of Algorithms*, 8(1):39–52, 1987.
- [Viz64] V. G. Vizing. On an estimate of the chromatic class of a p-graph. *Discret Analiz*, 3:25–30, 1964.